

* Depending on the type of product, specifications and infeed

Type	D 4/2	D 4/4	D 4/6
Capacity	1.000 kg/hr*	2.000 kg/hr*	3.000 kg/hr*
Product infeed	Continuous - dosed		
Dimensions	4000 x 1200 x 3000 mm	4000 x 1600 x 3000 mm	4000 x 2000 x 3000 mm
Amount of lanes	2	4	6
Installed power	2,25 kW, 230/400 V, 50/60 Hz		4 kW, 230/400 V, 50/60 Hz
Materials	AISI 304 Stainless Steel, glass blasted. Stainless Steel hollow shaft SEW drive, IP56, OS2, Food-Grade oil.		

* Depending on the type of product, specifications and infeed

** Capacity especially for the exclusive type: **oversize halving machine**

Type	DC 2/2	DC 2/4	DC 2/6
Capacity	750 kg/hr*	1.500 kg/hr*	2.250 kg/hr* 10.000 kg/hr**
Product infeed	Continuous - dosed		
Dimensions	4000 x 1200 x 3000 mm	4000 x 1600 x 3000 mm	4000 x 2000 x 3000 mm
Amount of lanes	2	4	6
Installed power	2,2 kW, 230/400 V, 50/60 Hz		4 kW, 230/400 V, 50/60 Hz
Materials	AISI 304 Stainless Steel, glass blasted. Stainless Steel hollow shaft SEW drive, IP56, OS2, Food-Grade oil.		